

## SPEC OIL STOU 15W40 & 20W40

### DESCRIPTION

SPEC OIL STOU is an agricultural stable multigrade oil, formulated from HVI base oils with a VI improver, plus a high performance detergent/dispersant additive. The oil is designed primarily for use in both normally aspirated and turbo-charged diesel engines, most transmissions and hydraulic systems found on modern agricultural implements. The load-carrying properties of the oil have been enhanced to ensure protection of the mating gear teeth even under the most arduous conditions. To provide the necessary lubrication for oil-immersed brakes, as found in some transmission systems used on tractors, an effective anti-squawk agent is incorporated.

### APPLICATION

SPEC OIL STOU is designed for use in both naturally aspirated and turbo-charged engines, most transmissions and hydraulic systems found on modern agricultural implements on the farm.

### PERFORMANCE

MEETS OR EXCEEDS:

- MASSEY FERGUSON CMS M1144, 1143, 1139 AND 1145
- AFNOR NFE 68603 E
- CG4, ACEAE3, SF, CF4
- JOHN DEERE J27 AND J20C
- FORD M2C – 159B/C
- FORD M2C 134 D
- ZF TE ML 06A, B (ALSO INCLUDES ZF TE ML06R), C AND 07B
- CASE NEW HOLLAND MAT 3525 AND 3526
- NEW HOLLAND 82009201/2/3
- CCMC D4
- API GL-4
- MERCEDES BENZ 227.1
- SPERRY VICKERS / EATON I-280-5 AND M2950 5
- MAN 271
- NEW HOLLAND NH030 AND NH 024C
- NEW HOLLAND NH 410 B AND NH 420 A
- ALLISON C-4
- TEML 03A, 05K, 06AB
- SAUER SUNSTRAND / DANFOSS NFE 68603 E

# SPEC OIL

## ADVANTAGES

- One oil for the farm
- Superior lubrication
- Protection against low temperature sludge and ring sticking
- Protection against rusting, foaming and corrosive wear
- Effective ant-squawk properties

## TYPICAL PHYSICAL CHARACTERISTICS

SAE Viscosity Grade	15W40	20W40
Viscosity 40 ° C	105	127
Viscosity 100 ° C	14.4	14.5
Viscosity Index	140	114
Pour Point	-27	-27
TBN mg KOH/g	10.66	10.66