

TECHNICAL DATA SHEET

SPEC OIL ANTIFREEZE 50/50 PREMIX

AND SUMMER COOLANT

Premium Quality ready to use Antifreeze

Description

PREMIX ANTIFREEZE is a 50 / 50 premix of Mono ethylene glycol and deionized water ready to use antifreeze and summer coolant containing a wide spectrum of corrosion inhibitors.

Outstanding Features

ANTIFREEZE has the following features:

- Effective protection against cold
- Broad spectrum corrosion inhibitors
- Concentrated

Specifications

ANTIFREEZE has the following OEM specifications:

- MB 235.0
- Broad spectrum corrosion inhibitors
- Concentrated

ANTIFREEZE is for use in the cooling systems of motor vehicles and stationary engines, which use water as the coolant. Its high concentration of Mono ethylene glycol enables the product to protect to low temperatures at high levels of dilution. Its broad spectrum of corrosion inhibitors ensures that no corrosion takes place in iron or aluminum components, thus giving long life. For maximum protection, a mixture of 50% ANTIFREEZE and 50% water is recommended.

Technical Data

Density @ 20°C kg/l	1.125
Freezing Point 50% Solution in Water	-18°C

Pack Sizes

210 Lt Drum
20 Lt Pail
5 Lt Bottle

TECHNICAL DATA: REVISED: 01/01/2019